

FSD 5056 E/B

Scrubber Dryer

Features

- Productivity of 2100 m²/h.
- Large fresh and Dirty Water Tank.
- Walk Behind Scrubber Dryer Scrub, Vacuum and dry the floor with one go.
- Cleaning efficiency is increased due to brush Diameter upgraded, Simple Operational Panel.



Accessories



Brush



Squeegee

Optional Accessories



Main Brush



Side Brush

Application Area



Epoxy Resin

Concrete Floor

Admin Area



Wooden Floor

Parking

Warehouse

Technical Specifications

Description	FSD 5056 E	FSD 5056 B
Solution Tank (l)	50	50
Recovery Tank (l)	56	56
Productivity (m ² /h)	2100	2100
Brush Motor (w)	550	550
Suction Motor (w)	550	550
Scrubbing Width (mm)	530	530
Suction Width (mm)	780	780
Brush Speed (RPM)	180	180
Brush Pressure (kg)	30	30
Brush Size (In)	20	20
Voltage (V/Hz)	220/50	DC 24V
Cable Length (m)	20	-
Battery Specs(V)	-	2*12V
Dimensions (cm)	129x59x107	129x59x107
Working Time	Continuous	3.5-4 h
Machine Weight(kg)	90	90
Noise (dB)	<65	<65

Clean and Green Emprise

D-313, M Cube Business Hub, Near Bombay Restaurant, Balitha, Vapi, Gujarat 396191, India
 Mobile No :- +91 7222947412, 63550 53082 Email :- marketing@cleanandgreen.in, www.cleanandgreen.in